



EvoLution Series

Tube Integrated Amplifiers

EVO 100-1

EVO 200-1

EVO 300-1

EVO 400-1

Version 2.2 – Feb 19, 2019





PrimaLuna®

EvoLution Series

Table of Contents

Thank You!	3
Specifications	4ABCD
Warning - Package Contents - Initial Setup	5
Front and Back Panel Inputs, Outputs, Controls & Remote Function	6AB
Remote Control	7
Headphone Output Connection	8
Adaptive Auto Bias™ - Bias Switch	9
Home Theater Through - Ultralinear – Triode	10
PhonoLogue Chassis - PhonoLogue Board	11
Tube Basics	12
Fuse Protection - Electronic Protection	13
Troubleshooting	14
Warranty Information	15
PrimaLuna Name & More	16

Copyright Durob Audio BV – 2019. All rights reserved.

Reproduction in whole or part of text, logo, graphics or schematics is strictly forbidden without permission, in writing, of Durob Audio BV.

The information in this manual is subject to change without further notice.



PrimaLuna®

EvoLution Series

Thank You!

We would like to thank you for choosing one of our PrimaLuna EVO Tube Integrated Amplifiers as the heart of your music system. The EVO Tube Integrated Amplifiers are the newest versions of the original first members of our family of affordable, high-quality tube products. The designers and builders of the PrimaLuna equipment all have a long history in high-end audio. We feel we have shown with PrimaLuna that we are able to offer a range of affordable yet elegant audio instruments that can easily compete with today's most expensive brands and we assure you we will continue that way. We firmly believe that our quality level will set the bar at a difficult height for other products to match.

This PrimaLuna EVO Tube Integrated amplifiers feature:

- Hand-made construction of a heavy-gauge, fully-vented steel chassis with a five coat finish, each coat hand-rubbed and polished, holding the finest point-to-point wiring, using workmanship that is normally only available at the highest price.
- Elegant style, heavy-metal remote controls.
- Premium parts that include toroidal and EI transformers for power supply; custom designed -in conjunction with one of the most prestigious transformer designers in the USA- encapsulated output transformers for lowest hum; wide bandwidth for great bass and extended highs; ceramic tube sockets; ALPS volume control; Nichicon and DuRoch capacitors; superfast Philips-rectifier-circuitry; gold-plated heavy-duty WBT style speaker terminals (all speaker connectors are solid shaft for better conductance, better sound, and higher reliability); gold-plated panel mounted RCA input jacks.
- Each EVO Tube Integrated Amplifier is as well a high-quality EVO Tube Headphone Amplifier!
- A 100% shielded Phono chassis for mounting our optional MM PhonoLogue circuit.
- SoftStart™ circuit for extended life of sensitive components, plus a reduced chance of tube failure from thermal shock.
- The newest generation Adaptive Auto Bias™ exclusive to PrimaLuna. This circuit monitors and smoothly adjusts bias constantly and instantly, reducing maintenance and increasing performance due to the dramatic reduction in distortion. It comes with a new extensive output stage protection circuitry with +B relay to protect output transformers, resistors and high voltage power supply in case a tube fails.
- The EVO Tube Integrated Amplifiers come with a High/Low bias switch. This means that with the flip of a switch you can choose for the optimum bias setting for EL34 type of tubes or KT88 type of tubes. No hassle with screwdrivers, no messing around with meters etc. Just switch tubes, switch bias!
- All PrimaLuna power transformers include the PTP™ (Power Transformer Protection) circuit. When the power transformer overheats due to environmental circumstances, overloading or some problem in the unit, an internal thermal switch breaks the primary, allowing the unit to cool down before harm is done. After it's cooled, contact is restored and if nothing is broken, the amp will repower and function properly.
- LIVE side of the AC input connector indicated by aluminium color screw.

We hope that our PrimaLuna EVO Tube Integrated amplifiers will make you want to follow our next steps in expanding our range of products. If you have any questions or comments, don't hesitate to contact us. You can also share your thoughts with others, for example at the [FaceBook PrimaLuna Amplifiers Owners Group](#) or other review sites.

We keep our prices low by relying on word-of-mouth and customer feedback, and we would appreciate hearing what you have to say about our product. Finally, if you need service during or after the warranty period, please don't hesitate to contact us.

Thanks again for your support!

Herman van den Dungen
DUROB AUDIO BV



PrimaLuna®

EvoLution Series

Specifications	Model EVO 100-1 for EL34 / KT88
Power UL	40 / 41 Watts per channel
Frequency Response	10 Hz – 32 kHz +/- 1 dB 10 Hz – 75 kHz +/- 3 dB
THD with AAB	< 0.2% @ 1W; less than 2% at rated power
S/N Ratio	90 dB / 91 dB
Input Impedance	100 kOhm
Input Sensitivity	260 / 280 mV (for rated power at maximum volume setting)
Maximum Gain	37 dB / 37.5 dB (EL34 / KT88)
Power Consumption	270 Watts / 280 Watts
Weight	Net weight: 39.6 lbs / 18 kg Shipping Weight: 46.2 lbs / 21 kg
Dimensions	15.9" x 11" x 7.5" / 405 mm x 280 mm x 190 mm (L x W x H)
Shipping Dimensions	18.4" x 15.2" x 12.2" / 468 mm x 385 mm x 315 mm (L x W x H)
Inputs	4 pairs Stereo RCA
Outputs	4 & 8 Ohm Speaker Taps, Tape, Headphone
Tube Complement	4 x EL34, 2 x 12AX7, 2 x 12AU7
Damping Coefficient	4 KD (1 kHz)

All PrimaLuna products come with PrimaLuna Silver Label tubes which are pre-selected by us following our simple 60 out of 100 rule (PTS™ - Premium Tube Selection) and as such, are already “special” when compared to other standard tubes on the market.



PrimaLuna®

EvoLution Series

Specifications	Model EVO 200-1 for EL34 / KT88
Power UL	44 / 45 Watts per channel
Frequency Response	10 Hz – 65 kHz +/- 1 dB 9 Hz – 95 kHz +/- 3 dB
THD with AAB	< 0.2% @ 1W; less than 2% at rated power
S/N Ratio	86 dB / 87 dB – 95 / 96 dB A Weighted
Input Impedance	100 kOhm
Input Sensitivity	275 / 285 mV (for rated power at maximum volume setting)
Maximum Gain	35 dB / 35.2 dB
Power Consumption	280 Watts / 290 Watts
Weight	Net weight: 52.8 lbs / 24 kg Shipping Weight: 61.6 lbs / 28 kg
Dimensions	15.9" x 14.4" x 8.1" / 405 mm x 365 mm x 205 mm (L x W x H)
Shipping Dimensions	22.7" x 18.4" x 12.4" / 577 mm x 468 mm x 315 mm (L x W x H)
Inputs	4 pairs Stereo RCA, 1 pair Home Theater Input
Outputs	4 & 8 Ohm Speaker Taps, Tape, Headphone
Tube Complement	4 x EL34, 4 x 12AU7
Damping Coefficient	4 KD (1 kHz)

All PrimaLuna products come with PrimaLuna Silver Label tubes which are pre-selected by us following our simple 60 out of 100 rule (PTS™ - Premium Tube Selection) and as such, are already “special” when compared to other standard tubes on the market.



PrimaLuna®

EvoLution Series

Specifications	Model EVO 300-1 for EL34 / KT88 / KT120 / KT150
Power UL	42 / 43 / 45 / 48 Watts per channel
Power TR	24 / 25 / 27 / 30.5 Watts per channel
Frequency Response	10 Hz – 50 kHz +/- 1 dB 8 Hz – 75 kHz +/- 3 dB
THD with AAB	< 0.2% @ 1W; less than 2% at rated power
S/N Ratio	86 dB / 87 dB / 87 dB / 87 dB
Input Impedance	100 kOhm
Input Sensitivity	270 / 285 / 290 / 300 mV for rated power at max volume setting
Maximum Gain	36.5 dB / 36.7 dB / 36.8 dB / 36.9 dB
Power Consumption	290 Watts / 300 Watts / 330 Watts / 340 Watts
Weight	Net weight: 68.2 lbs / 31 kg Shipping Weight: 77 lbs / 35 kg
Dimensions	15.9" x 15.2" x 8.1" / 405 mm x 385 mm x 205 mm (L x W x H)
Shipping Dimensions	22.7" x 18.4" x 12.4" / 577 mm x 468 mm x 315 mm (L x W x H)
Inputs	5 pairs Stereo RCA, 1 pair Home Theater Input
Outputs	4 & 8 Ohm Speaker Taps, Tape, Stereo/Mono Sub, Headphone
Tube Complement	4 x EL34, 6 x 12AU7
Damping Coefficient	4 KD (1 kHz)

All PrimaLuna products come with PrimaLuna Silver Label tubes which are pre-selected by us following our simple 60 out of 100 rule (PTS™ - Premium Tube Selection) and as such, are already “special” when compared to other standard tubes on the market.



PrimaLuna®

EvoLution Series

Specifications	Model EVO 400-1 for EL34 / KT88 / KT120 / KT150
Power UL	70 / 72 / 85 / 88 Watts per channel
Power TR	38 / 40 / 45 / 50 Watts per channel
Frequency Response	9 Hz – 50 kHz +/- 1 dB 8 Hz – 68 kHz +/- 3 dB
THD with AABB	< 0.1% @ 1W; less than 2% at rated power
S/N Ratio	90 dB – 98 dB A Weighted
Input Impedance	100 kOhm
Input Sensitivity	320 / 320 / 360 / 370 mV for rated power at max volume setting
Maximum Gain UL	37 dB / 37.5 dB / 37.5 dB / 36.9 dB
Maximum Gain TR	36.5 dB / 36 dB / 36 dB / 36 dB
Power Consumption	470 Watts / 480 Watts / 540 Watts / 550 Watts
Weight	Net weight: 68.2 lbs / 31 kg Shipping Weight: 79.2 lbs / 36 kg
Dimensions	15.9" x 15.2" x 8.1" / 405 mm x 385 mm x 205 mm (L x W x H)
Shipping Dimensions	22.7" x 18.4" x 12.4" / 577 mm x 468 mm x 315 mm (L x W x H)
Inputs	5 pairs Stereo RCA, 1 pair Home Theater Input
Outputs	4 & 8 Ohm Speaker Taps, Tape, Stereo/Mono Sub, Headphone
Tube Complement	8 x EL34, 6 x 12AU7
Damping Coefficient	7 KD (1 kHz)

All PrimaLuna products come with PrimaLuna Silver Label tubes which are pre-selected by us following our simple 60 out of 100 rule (PTS™ - Premium Tube Selection) and as such, are already “special” when compared to other standard tubes on the market.



PrimaLuna®

EvoLution Series

Warning

To prevent serious injury, electrical shock or fire:

- Do not operate with the bottom plate removed. Keep away from rain and moisture.
- Disconnect the ac mains cable before changing fuses and/or tubes.
- Do not replace fuses with any fuse other than the same type and rating as used by the factory.
- Do not replace tubes without reading instructions.
- Do not replace fuses or tubes if you have any doubt about your ability to do so.
- We accept no responsibility for any personal or material damage due to incompetent use or users.

Package Contents

EVO Tube Integrated Amplifier	1 piece
EVO Remote Control	1 piece
Power Cord	1 piece
This Owner's Manual	1 piece
White Gloves	1 pair
Tube Complement	See specification pages
Spare Mains Littelfuse Model 213 fuse	1 piece
Spare Adaptive Auto Bias Littelfuse Model 213 fuse	1 piece





Initial Setup

- Don't wear a watch or rings and carefully remove the EVO Tube Integrated Amplifier from its packaging. Once the plastic bag has been removed, use the white gloves provided to prevent fingerprint smudges.
- Remove the tube cage by carefully pulling it up and away from the amplifier.
- Remove the protective foam surrounding the tubes.
- Tubes are already installed.
- Check that each tube is firmly and straightly seated in its socket. Use gloves provided.
- Replace cage back in its place if desired.
- Check to see the power switch is off (down) and the bias-selector switch is in the correct position.
- Connect each source to the corresponding plugs.
- Connect your speaker wires, positive to positive, negative to negative. This unit is non-inverting.
- Plug the power cord into the amplifier, then into the wall socket.
- Switch sources on and then switch the amplifier on.
- The tubes will be warmed up and ready to use in about 60 seconds.

PrimaLuna®

EvoLution Series

Front Panel Outputs, Controls & Remote Function




PrimaLuna front panels are made from machined aluminium, finished to match the black/blue metallic chassis. The volume is controlled with the knob on the left, source selection is on the right. Both volume and source can also be selected by remote control. Your sources are labeled AUX 1, AUX 2, etc (no functional differences between these) and eventually HT. The headphone output is on the bottom right side. The heavy metal remote control that comes with your PrimaLuna EVO Tube Integrated Amplifier can be used for selecting sources and adjusting volume. It also can be used to control functions on all PrimaLuna CD players. The power switch and auto bias fuse are located on the left side of the amp, just behind the front plate, the bias and headphone/loudspeaker switch on the right side, just behind the front plate.

PrimaLuna[®]

EvoLution Series

Back Panel Inputs, Outputs




At the rear panel, you will find your inputs, eventually the HT Pass Thru, the speaker terminals, Tape Out and Sub Out. Attach the (+) from your loudspeaker to the 4 or 8 Ohm terminal that most closely matches the average impedance of your loudspeakers according to their manufacturer's specifications. The (-) from your loudspeaker attaches to the 0 Ohm terminal. Experiment using the 4 or 8 Ohm (+) terminal to find what's the best match with your speakers. Don't make any assumptions. Trust your ears.

PrimaLuna®

EvoLution Series

Remote Control



Attention! Due to increasingly stringent safety measures, it can happen that the remote control arrives without batteries installed.

The functions of the EVO Tube Integrated Amplifier Remote Controls are self-explanatory. It controls source selection, volume & mute functions. The remote will also control the basic functions of the PrimaLuna CD players.

The EVO Tube Integrated Amplifier Remote Controls have two high-quality silicon rubber rings on each end to protect it from becoming damaged or damaging your furniture. These rings can be easily removed in case batteries have to be replaced.

In the event your remote control does not function, please first check the battery/batteries. To access the battery compartment, remove the rubber rings and unscrew the back plate.

Do NOT use rechargeable batteries!


You can also check your remote here:
<https://primalunablog.com/?s=remote>

If the remote still does not function, contact your dealer for further assistance.

PrimaLuna®

EvoLution Series

Headphone Output Connection



Owners of a PrimaLuna EVO Tube Integrated Amplifier own also one of the best headphone amps in the world. And maybe the only amp that lets you listen with either the warmth of tubes at the flip of a switch!

On the right side of the front panel, you find the output connector for your headphones, while just behind the front panel on the right side you find the switch to select for loudspeakers (LS) or headphones (HP).

Most tube integrated amps and preamps use a solid-state op-amp chip for running headphones. Stand-alone tube headphone amps will vary in quality like any other tube amp.

Headphones are simply small speakers that require less power. Some amps will use smaller output tubes that groan to have enough dissipation to run power-hungry planar headphones.

Other brands, including those costing double or triple or more, will use larger output tubes, then use a voltage divider network to drop the power down to an acceptable level for headphones. This is how PrimaLuna designed the headphone circuit. We simply took advantage of the fact that we have the best tube integrated amplifiers on the market. What is good enough for your living room speakers is also good for your “earspeakers”.


Now there is no immediate need to pay for a separate state of the art headphone amp. Our Integrated (Headphone) Amplifiers are the favorite of owners who use everything from Audeze to Hifiman to Sennheiser!

- If you switch from Loudspeakers to Headphone, always first turn down your volume.
- Don't use the Headphone switch with no headphone connected.
- Listening at a high volume can damage your hearing.
- In case you are in doubt if you own over hungry headphones, like for example Abyss 1266 or HIFIMAN SUSVARA, please contact us for information/modification of the circuit.

PrimaLuna®

EvoLution Series

Adaptive Auto Bias™



Our PrimaLuna exclusive Adaptive Auto Bias™ circuit monitors and smoothly adjusts bias constantly and instantly, reducing maintenance and increasing performance due to the dramatic reduction in distortion. The genius of this design is that the Adaptive Auto Bias™ actually improves the overall sound quality and performance of the amp. Between 12 and 30 Watts, measured distortion levels drop by over 40%. In addition, tubes do not have to be matched, and there are no bias (re-)adjustments needed, ever. The new generation Adaptive Auto Bias™ circuit comes with a new extensive output stage protection circuitry with +B relay to protect output transformers, resistors and high voltage power supply in case a tube fails. This circuit is also protected with an easily accessible fuse located next to the on / off power switch.



Bias Switch

The EVO Tube Integrated Amplifiers come with a bias level switch. This means that by the flip of a switch you can choose the optimum bias setting. Low Bias for EL34s (or equivalent tubes) or High Bias for KT88s, KT120s or KT150s (or equivalent tubes). No hassle with screwdrivers, no messing around with meters etc. If you swap tubes, simply flip the switch -with volume down!- for optimum bias!

Should you use the “wrong” bias setting for the tubes in use, don’t worry. It just means you did not choose the “optimum” bias setting as decided by the PrimaLuna design team.



PrimaLuna®

EvoLution Series

Stereo Home Theater Pass Thru

Your PrimaLuna Tube Preamplifier or Integrated Amplifier might be equipped with a home theater pass thru that allows you to enjoy your stereo source material and the 2 main channels of your separate home theater processor. The home theater passes thru completely removes the preamp section from the signal path.

Connecting Your Surround Sound Component

To avoid damaging your equipment, always make sure everything is turned off and unplugged from the wall before connecting your components. Connect your stereo sources and speakers as normal.

To integrate your PrimaLuna Tube Preamplifier or Integrated Amplifier into your home theater system, take the front left & right preamp outputs from your A/V processor or receiver and plug them into the “HT” input on the back of the PrimaLuna Tube Preamplifier or Integrated Amplifier.

When you want to watch a movie, simply turn the PrimaLuna Tube Integrated Amplifier on, and switch the input to “HT.” **Attention: double-check if the volume of your home theatre processor is at minimum!** Now control the volume via your home theater processor as normal.

We recommend you go into the setup menu of your processor to match the levels of the front Left & Right speakers to match the volume of your center channel. Consult your processor’s manual for more information.

Ultralinear – Triode Switching

Your EVO 300 and 400 integrated amplifier affords you the opportunity of switching between Ultralinear and Triode modes by remote control. You need not turn off the amp to do so; you can switch while the unit is operating. Although a faint click might be heard through your speakers, it is in no way harmful. Your DiaLogue Premium always starts in Ultralinear mode when powered up. Centered behind the front panel is a two-color LED which indicates the mode in which the amp is functioning: Red—Ultralinear; Green—Triode.


Ultralinear Mode - Triode Mode

The term ultralinear design exerts a tighter grip on the speakers and produces music more likely to be described as accurate, dynamic, with great inner detail. The top and bottom end take on more “pop” and excitement. Triode sound is best described as warmer on top and bottom, a little compressed, with the midband now slightly more pronounced. The sound is more relaxed. In absolute terms it will not play as loud as maximum power drops by roughly half compared to Ultralinear.

PrimaLuna[®]

EvoLution Series

PhonoLogue Chassis (standard)




Every EVO Integrated Amplifier and Preamplifier comes standard with an extra chassis mounted on the bottom plate. This extra chassis is meant for installation of our MM PhonoLogue board. It provides extra space, which is in most PrimaLuna EVO models not available anymore and it provides an extra shielded environment for less hum and noise mounting of the sensitive phono stage.

PhonoLogue MM Board (optional)

Our PhonoLogue phono stage can be installed at any time by your dealer or any qualified person. Ask for the PhonoLogue installation bulletin.

The PhonoLogue MM phono stage with RIAA equalization takes the place of the AUX2 input. It provides superior sound quality on a tiny footprint. We use Surface Mount Technology implementation for shortest signal paths as well as minimum parasitic capacitances and inductances. Excellent parts throughout, selected on sound quality as first priority: miniature film capacitors, minimef resistors, superior opamp for highest accuracy, lowest noise, highest speed and most robust drive capabilities into the RIAA correction stage, resulting in a very detailed, open and lifelike sound from any LP record. Low impedance electrolytics, super low-noise power supply. Dimensions: small as a big stamp!



Specifications:

- Frequency Response: 10Hz - 50kHz
- Input Impedance: 50 kOhm
- Gain: 42dB (127x)
- RIAA accuracy: <0,5B 20Hz - 20kHz
- Overload Margin: >20dB rel 5mV
- Harmonic Distortion & noise: -83dB
- Size: 3.2 x 3.8 cm (1.26" x 1.5")

PrimaLuna®


EvoLution Series

Tube Basics

The 12AX7 and 12AU7 tubes will have a life of about 5,000 to 10,000 hours. However, the life span of power tubes is more difficult to predict. It greatly depends on how "gently" or "roughly" you use your amplifier. In general, under normal conditions, you can figure between 2,000 and 3,000 hours.

Here are some guidelines on using tubes:

- Do not use treatments on tube pins or in sockets.
- If you decide to experiment with other tube types, it's best not to swap tubes in and out repeatedly. To do so requires you to turn your amplifier off and on and you never want to cycle amplifiers on and off rapidly. They should be left off for at least five minutes. Further, every time you insert a tube, you stand a chance of loosening the tube sockets. It's okay to have fun, and we support that, but don't go crazy and swap tubes in and out twenty times a day.
- Do not leave the amplifier on 24 hours a day. Just a short warm-up is required for the PrimaLuna to get into its groove.
- Break-in yields improvements. Every tube, when new, needs to be left alone for a little while. So, when your amplifier is new, or when you re-tube it, allow a little time to settle in. There is, however, no fixed "time rule" for break-in.
- Tubes can vary electrically, and by plugging in the wrong type of tube you can damage the amplifier and void your warranty.
- Please note to use same type or equivalent tubes for a replacement!




Some tubes and tube sockets have a "center key" which must line up! If you misalign them and use brute force, you will damage important and expensive parts of your amplifier!!

PrimaLuna[®]

EvoLution Series

Fuse Protection


Warning! Fuses are safety valves. They should always be replaced with the exact same value and type. Never attempt to check or replace a fuse while the amp is plugged in. Turn it off and unplug the AC cord before continuing. Wait 10 minutes to let tubes cool down and the circuit to fully discharge.



Mains Fuse: The mains fuse is located on the rear of the amplifier, just below the power cord socket (see picture on the left). The fuse rating is 1 x Littelfuse 213 Series 3.15A Slow Blow 5 x 20mm fuse for 100-125VAC and Littelfuse 213 Series 1.6A Slow Blow 5 x 20mm fuse for 200-250VAC. Always replace with the same type and value fuse! The fuse holder can be opened using a small slotted flat blade screwdriver.

The IEC connector is mounted with 2 different color screws. One silver, one black. The silver screw indicates the Live AC in the IEC connector. It helps with the "correct" connection to AC. Nevertheless always check the AC cable by measuring as not every AC cable is constructed the same way.

The Adaptive Auto Bias Board is protected with an easily accessible Littelfuse 213 315mA fuse located next to the on / off power switch on the left side of the Amplifier, just behind the front.



Electronic Protection

The PrimaLuna EVO Tube Integrated Amplifiers are equipped with Soft Start™ and come with an extensive output stage protection circuitry with +B relay to protect output transformers, resistors and high voltage power supply in case a tube fails.

The board also comes with a BTI™ circuit. BTI™ stands for Bad Tube Indication (by the change of front LED to red), making tube-life again a bit easier. The BTI™ circuit is totally inactive during normal operation. However when one (or more) output tube(s) draw(s) significantly more current than normal for a couple of seconds, such as when a loudspeaker terminal short-circuits with volume turned up, or in the case of an output tube failure, the BTI™ circuit "reads" the changes as a potential threat and as a protective measure, interrupts the power supply. It indicates, by the led in front of the power tube, which tube might be bad. To reset, simply turn the power off and after two minutes, turn back on. **However**, you do not want to repower the unit until the cause of the failure has been identified and resolved. Switching the power back on too early also can fool the BTI circuit into acting as though the problem has not been totally resolved and it may put the amp back into protection mode again. So be sure to give it enough time to reset!



PrimaLuna®

EvoLution Series

Troubleshooting Tips

No output. The power switch is on, but the power LED is off and tubes do not light up.

- *AC cable makes a bad connection in the IEC connector. Please check.*
- *Mains fuse is broken. Please check.*
- *PTP™ (Power Transformer Protection) protection may have switched off the power transformer. If so, the amplifier will switch on again after the internal temperature of the power transformer returns to normal. Overheating might be caused by higher environment temperature than normal or heavy use.*

No output. The power switch is on, the front LED is green and tubes do light up.

- *Adaptive Auto Bias Board fuse is broken. Please check.*

No output. The power switch is on, the front LED is red and LED in front of a power tube MIGHT light up.

- *BTI™ circuit has switched off the high voltage supply to the power output tubes. This can happen for example, when one (or more) output tube(s) draw(s) significantly more current than normal, like what can happen when a loudspeaker terminal is short-circuited with the volume turned up.*
- *In case of an internal output tube failure, the BTI™ circuit understands that there is a new situation which can cause harm to the amplifier or the loudspeaker, and the high voltage power supply to the output tubes is interrupted as a protective measure. The front LED will turn red and you might see a red LED in front of one or more power tubes. To reset, switch the amplifier's power off for at least two minutes, then switch back on. Of course, this should only be done after the cause of the failure has been identified and resolved. Switching the power back on too early can fool the BTI™ circuit into acting as though the problem has not been totally resolved and it may put the amp back into protection mode again. So be sure to give it enough time to reset.*

Noise or hum coming from one channel (eventually when you change your volume setting).

- *Noisy tube. At first swap the two inner small tubes left to right. If noise follows the tube swap then you have found the problem tube. If noise does not follow, swap the next set of two small tubes left to right, eventually the next set in case your amplifier has 6 small tubes.*
- *Possible bad output tube. Swap the output tubes in pairs from right to left. If hum follows the swap, swap the far left and far right tubes. If the hum returns to the original problem channel, you have found the problem tube. If not, swap the inside output tubes left to right.*

Noise/distortion coming from both channels.

- *Tubes may be in need of replacement.*



PrimaLuna®

EvoLution Series

Warranty Information

Two-year limited warranty

Six-month warranty on stock vacuum tubes

Terms & Conditions

- 1. Limited to the original purchaser.** This warranty is for the sole benefit of the original purchaser of the covered product, and may not be transferred to a subsequent owner.
- 2. Conditions & Limitations.** This warranty is subject to conditions and limitations, as follows. This warranty is void and inapplicable if the product has not been used in accordance with the instructions found elsewhere in this manual, or if it has been misused, abused, damaged by accident or neglect, or in transport once in possession of purchaser. The warranty is also void if the product has been tampered with or has been repaired or modified by anyone other than Durob Audio BV or its specifically authorized representatives.
- 3. Remedy.** If this product contains material, manufacturing, or workmanship defects, it must be packed in original packaging and returned to Durob Audio BV or its authorized representative via insured freight, at the owner's expense. Returned products must be accompanied by a written description of the defect, and a return authorization number (available from Durob Audio BV or the authorized representative via e-mail). Upon receipt of the defective product, Durob Audio BV or the authorized representative agrees to repair the product without charge for parts (except vacuum tubes if the unit is more than 6 months old), or labor. The product will then returned via prepaid, insured freight, with the carrier at the sole determination of Durob Audio BV or the authorized representative. This constitutes the purchaser's sole remedy.
- 4. Design change.** Durob Audio BV and its partners reserve the right to modify their products or change specifications at any time without obligation or liability to previous purchasers.
- 5. Miscellaneous.** Any implied warranties relating to the above product shall be limited to the duration of this warranty. This warranty does not extend to any identical or consequential costs or damages to purchaser or third-parties. Our liability will be no more than the amount you paid for the product that is the subject of a claim. This is the maximum amount for which we are responsible. This warranty gives you specific legal rights. You may also have other rights which vary from country to country and state to state.



PrimaLuna®

EvoLution Series

PrimaLuna Illumination

Herman van den Dungen: **PrimaLuna** ► *in the Italian language is "First Moon". My grandfather was the first "Herman". My grandmother, an aristocratic lady in a small Dutch village, had a special name for her husband: "Maontje", which means Little Moon (which became also the name of our small dog), van den Dungen. The people in the village adopted that name, and having a strong accent, they soon called him "Maontje" van den Dungen. My father's first name was Cor, but in the village, it was of course "Cor from Maontje van den Dungen". I was of course "Herman from Cor from Maontje van den Dungen" etc. That's why I thought of **First Moon** as a brand name and that's why the logo is how it is◀*

Loris Arrigucci: **PrimaLuna** ► *believe it or not ... I discovered a small town located 50Km north of Milano called **Primaluna!!!** Please get yourself a map from Italy. You'll find **Primaluna** town near the upper-right corner. It is located 50Km north of Milano near the Lake of Como. This should eliminate every doubt regarding "Italian" origin of **Primaluna** name. I've read the "history" section of the **Primaluna** village web site and found the following (literally translated):*

*One probable interpretation of the name of the village comes from Latin "**Primum Lumen**", which means "**First Light**" of Christianity since the very first evidence of Christianity in this region dates 495 Annus Domini. "**First Light**" translates into "**Prima Luce**" in Italian and this seems very interesting to me: **PrimaLuce (FirstLight)** is the first light that we, hi-fi lovers with small budgets, can see in this world of darkness populated by way too expensive esoteric gears◀*



Please contact us for registering your **PrimaLuna EVO** tube product. We will keep you updated on any upgrades or any other information related to your product. If you wish to comment on your **PrimaLuna EVO** tube product, please do. If you want to send us a review of your experience with the amplifier, you are more than welcome to. If you want to discuss with other **PrimaLuna** owners, join the completely independent [FaceBook PrimaLuna Amplifiers Owners Group](#). If you have any technical questions, please don't hesitate to contact us. We thank you upfront for your time and attention.

National distribution:

Worldwide distribution:

Durob Audio BV
P.O. Box 109
5250 AC Vlijmen
The Netherlands

Email: primaluna@primaluna.nl

Website: www.primaluna.nl